

EnviraSlim Awning Windows

Thermally broken aluminium



CODE PREFIX: WTBAW

Size Code		04	06	07	09	11	12	12	15	16	18	21	24	18	21	24	27
	Stud Opening (mm)	506	666	786	906	1146	1266	1266	1506	1626	1866	2226	2466	1866	2226	2466	2706
	Overall Reveal Size (mm)	486	646	766	886	1126	1246	1246	1486	1606	1846	2206	2446	1846	2206	2446	2686
	External Metal Size (mm)	450	610	730	850	1090	1210	1210	1450	1570	1810	2170	2410	1810	2170	2410	2650
	Brick Size	2	2.5	3	3.5	4.5	5	5	6	6.5	7.5	9	10	7.5	9	10	11
18	1866	1836	1800*	18													
20	2123	2093	2057*	20.5													
21	2166	2136	2100*	21													
23	2396	2366	2330**	23													

Not Available

- Additional configurations up to 6 lites across available.
- Available in 20mm double glazing.
- Size charts are provided as a guide only, images may not reflect the exact proportions of the product you specify.
- Images represent the external view of the product.

- Sizes shown are the standard offering for N2 areas, specific size limitations or alternative options may be applicable for other wind categories.

*Sash Height for 1800/2057/2100 is 1329.

**Sash Height for 2330 is 1499.

EnviraSlim Awning Windows – Multi Transom



Thermally broken aluminium

CODE PREFIX: WTBAW

Size Code		06	07	09	11	12	15	18
	Stud Opening (mm)	666	786	906	1146	1266	1506	1866
	Overall Reveal Size (mm)	646	766	886	1126	1246	1486	1846
	External Metal Size (mm)	610	730	850	1090	1210	1450	1810
	Brick Size	2.5	3	3.5	4.5	5	6	7.5
07	766	736	700	7				
10	1096	1066	1030	10				
12	1266	1236	1200	12				
14	1436	1406	1370	14				
14	1436	1406	1370	14				
15	1606	1576	1540	15.5				
18	1866	1836	1800	18				
20	2123	2093	2057	20.5				
20	2123	2093	2057	20.5				
23	2396	2366	2330	23				

- Available in 20mm double glazing.
- Size charts are provided as a guide only, images may not reflect the exact proportions of the product you specify.
- Images represent the external view of the product.
- Sizes shown are the standard offering for N2 areas, specific size limitations or alternative options may be applicable for other wind categories.

EnviraSlim Awning Windows – No Transom



Thermally broken aluminium

CODE PREFIX: WTBAW

Size Code		04	06	07	09	11	12	12	15	16	18	21	24	18	21	24	27	21	24	27
	Stud Opening (mm)	506	666	786	906	1146	1266	1266	1506	1626	1866	2226	2466	1866	2226	2466	2706	2226	2466	2706
	Overall Reveal Size (mm)	486	646	766	886	1126	1246	1246	1486	1606	1846	2206	2446	1846	2206	2446	2686	2206	2446	2686
	External Metal Size (mm)	450	610	730	850	1090	1210	1210	1450	1570	1810	2170	2410	1810	2170	2410	2650	2170	2410	2650
	Brick Size	2	2.5	3	3.5	4.5	5	5	6	6.5	7.5	9	10	7.5	9	10	11	9	10	11
06	666	636	600	6																
09	920	890	854	8.5																
10	1096	1066	1030	10																
12	1266	1236	1200	12																
14	1436	1406	1370	14																
15	1606	1576	1540	15.5																
18	1866	1836	1800	18																
20	2123	2093	2057	20.5																
21	2166	2136	2100	21																
23	2396	2366	2330	23																

Not Available

- Additional configurations up to 6 lites across available.
- Available in 20mm double glazing.
- Size charts are provided as a guide only, images may not reflect the exact proportions of the product you specify.
- Images represent the external view of the product.
- Sizes shown are the standard offering for N2 areas, specific size limitations or alternative options may be applicable for other wind categories.

EnviraSlim Fixed Windows



Thermally broken aluminium


CODE PREFIX: WTBAW

Size Code		04	06	07	09	11	12	12	15	16	18	21	24
	Stud Opening (mm)	506	666	786	906	1146	1266	1266	1506	1626	1866	2226	2466
	Overall Reveal Size (mm)	486	646	766	886	1126	1246	1246	1486	1606	1846	2206	2446
		External Metal Size (mm)	450	610	730	850	1090	1210	1210	1450	1570	1810	2170
		Brick Size	2	2.5	3	3.5	4.5	5	5	6	6.5	7.5	9
06	666	636	600	6									
09	920	890	854	8.5									
10	1096	1066	1030	10									
12	1266	1236	1200	12									
14	1436	1406	1370	14									
15	1606	1576	1540	15.5									
18	1866	1836	1800	18									
20	2123	2093	2057	20.5									
21	2166	2136	2100	21									
23	2396	2366	2330	23									

- Additional configurations up to 6 lites across available.
- Available in 20mm double glazing.
- Size charts are provided as a guide only, images may not reflect the exact proportions of the product you specify.

- Images represent the external view of the product.
- Sizes shown are the standard offering for N2 areas, specific size limitations or alternative options may be applicable for other wind categories.

- Raked windows are available, speak to your sales consultant about size limitations:



EnviraSlim Sliding Doors

Thermally broken aluminium



CODE PREFIX: DTBSL


Size Code		14	16	18	21	24	27	32	36	28	31	36	43	48
	Stud Opening (mm)	1506	1626	1866	2226	2466	2757	3297	3657	2900	3140	3620	4340	4820
	Overall Reveal Size (mm)	1486	1606	1846	2206	2446	2737	3277	3637	2880	3120	3600	4320	4800
	External Metal Size (mm)	1450	1570	1810	2170	2410	2701	3241	3601	2844	3084	3564	4284	4764
	Brick Size	6	6.5	7.5	9	10	11	13.5	15	12	13	15	18	20
21	2148	2118	2100	21										
	2448	2418	2400	24										

- Available in 20mm double glazing.
- Water penetration rating of 200pa maximum.
- Size charts are provided as a guide only, images may not reflect the exact proportions of the product you specify.
- Images represent the external view of the product.
- Sizes shown are the standard offering for N2 areas, specific size limitations or alternative options may be applicable for other wind categories.


Corner Door Option:

- Available in either 2/2 panel (sliding) or 3/3 panel (stacking) configurations.
- Available standard heights are 2100mm & 2400mm.
- 2 panel sliding internal or external corner doors maximum nominal width is 2410mm.
- Panels are available in Left Wing Active (LWA) or Right Wing Active (RWA) configurations. The active panel is selected as viewed from outside. The active panel will open first and includes the handle and lock.

Internal Sliding Corner Door



External Sliding Corner Door



EnviraSlim Stacking Doors

Thermally broken aluminium



CODE PREFIX: DTBSK


Size Code		21	24	27	32	36	42	46	53	
	Stud Opening (mm)	2190	2370	2730	3270	3630	4266	4626	5346	
	Overall Reveal Size (mm)	2170	2350	2710	3250	3610	4246	4606	5326	
	External Metal Size (mm)	2134	2314	2674	3214	3574	4210	4570	5290	
	Brick Size	9	9.5	11	13.5	15	17.5	20	22	
21	2148	2118	2100	21						
24	2448	2418	2400	24						

- Available in 20mm double glazing.
- Water penetration rating of 200pa maximum.
- Size charts are provided as a guide only, images may not reflect the exact proportions of the product you specify.
- Images represent the external view of the product.
- Sizes shown are the standard offering for N2 areas, specific size limitations or alternative options may be applicable for other wind categories.


Corner Door Option:

- Available in either 2/2 panel (sliding) or 3/3 panel (stacking) configurations.
- Available standard heights are 2100mm & 2400mm.
- 3 panel stacking internal or external corner doors maximum nominal width is 3574mm.
- Panels are available in Left Wing Active (LWA) or Right Wing Active (RWA) configurations. The active panel is selected as viewed from outside. The active panel will open first and includes the handle and lock.

Internal Stacking Corner Door



External Stacking Corner Door



EnviraLuxe Awning Windows

Thermally broken aluminium



CODE PREFIX: WTBAW

Size Code		04	06	07	09	11	12	12	15	16	18	21	24	18	21	24	27
	Stud Opening (mm)	506	666	786	906	1146	1266	1266	1506	1626	1866	2226	2466	1866	2226	2466	2706
	Overall Reveal Size (mm)	486	646	766	886	1126	1246	1246	1486	1606	1846	2206	2446	1846	2206	2446	2686
	External Metal Size (mm)	450	610	730	850	1090	1210	1210	1450	1570	1810	2170	2410	1810	2170	2410	2650
	Brick Size	2	2.5	3	3.5	4.5	5	5	6	6.5	7.5	9	10	7.5	9	10	11
18	1866	1836	1800*	18													
20	2123	2093	2057*	20.5													
21	2166	2136	2100*	21													
23	2396	2366	2330**	23													

Not Available

- Additional configurations up to 6 lites across available.
- Available in 20mm & 24mm double glazing.
- Size charts are provided as a guide only, images may not reflect the exact proportions of the product you specify.
- Images represent the external view of the product.

- Sizes shown are the standard offering for N2 areas, specific size limitations or alternative options may be applicable for other wind categories.

*Sash Height for 1800/2057/2100 is 1288.

**Sash Height for 2330 is 1458.

EnviraLuxe Awning Windows – Multi Transom



Thermally broken aluminium

CODE PREFIX: WTBAW

Size Code		06	07	09	11	12	18	21	24	27
	Stud Opening (mm)	666	786	906	1146	1266	1866	2226	2466	2706
	Overall Reveal Size (mm)	646	766	886	1126	1246	1846	2206	2446	2686
	External Metal Size (mm)	610	730	850	1090	1210	1810	2170	2410	2650
	Brick Size	2.5	3	3.5	4.5	5	7.5	9	10	11
07	766	736	700	7						
10	1096	1066	1030	10						
12	1266	1236	1200	12						
14	1436	1406	1370	14						
14	1436	1406	1370	14						
15	1606	1576	1540	15.5						
18	1866	1836	1800	18						
20	2123	2093	2057	20.5						
20	2123	2093	2057	20.5						
23	2396	2366	2330	23						

- Available in 20mm & 24mm double glazing.
- Size charts are provided as a guide only, images may not reflect the exact proportions of the product you specify.
- Images represent the external view of the product.
- Sizes shown are the standard offering for N2 areas, specific size limitations or alternative options may be applicable for other wind categories.

EnviraLuxe Awning Windows – No Transom



Thermally broken aluminium

CODE PREFIX: WTBAW

Size Code		04	06	07	09	11	12	12	15	16	18	21	24	18	21	24	27	21	24	27
	Stud Opening (mm)	506	666	786	906	1146	1266	1266	1506	1626	1866	2226	2466	1866	2226	2466	2706	2226	2466	2706
	Overall Reveal Size (mm)	486	646	766	886	1126	1246	1246	1486	1606	1846	2206	2446	1846	2206	2446	2686	2206	2446	2686
	External Metal Size (mm)	450	610	730	850	1090	1210	1210	1450	1570	1810	2170	2410	1810	2170	2410	2650	2170	2410	2650
	Brick Size	2	2.5	3	3.5	4.5	5	5	6	6.5	7.5	9	10	7.5	9	10	11	9	10	11
06	666	636	600	6																
09	920	890	854	8.5																
10	1096	1066	1030	10																
12	1266	1236	1200	12																
14	1436	1406	1370	14																
15	1606	1576	1540	15.5																
18	1866	1836	1800	18																
20	2123	2093	2057	20.5																
21	2166	2136	2100	21																
23	2396	2366	2330	23																

Not Available

- Additional configurations up to 6 lites across available.
- Available in 20mm & 24mm double glazing.
- Size charts are provided as a guide only, images may not reflect the exact proportions of the product you specify.
- Images represent the external view of the product.
- Sizes shown are the standard offering for N2 areas, specific size limitations or alternative options may be applicable for other wind categories.

EnviraLuxe Fixed Windows



Thermally broken aluminium

CODE PREFIX: WTBAW

Size Code		04	06	09	12	15	18	21	24	27	30	32	36	40	42	09	12	15	18	21	24	27	30	32	36	40	42		
Stud Opening (mm)	Overall Reveal Size (mm)	External Metal Size (mm)																											
		Brick Size																											
		Brick Size																											
		Brick Size																											
06	666	636	600	6																									
09	920	890	854	8.5																									
10	1096	1066	1030	10																									
12	1266	1236	1200	12																									
14	1436	1406	1370	14																									
15	1606	1576	1540	15.5																									
18	1866	1836	1800	18																									
20	2123	2093	2057	20.5																									
21	2166	2136	2100	21																									
23	2396	2366	2330	23																									
24	2436	2406	2370	24																									
27	2766	2736	2700	27																									
30	3066	3036	3000	30																									
40	4066	4036	4000	40																									

Not Available

- Additional configurations up to 6 lites across available.
- Available in 20mm & 24mm double glazing.
- Size charts are provided as a guide only, images may not reflect the exact proportions of the product you specify.

- Images represent the external view of the product.
- Sizes shown are the standard offering for N2 areas, specific size limitations or alternative options may be applicable for other wind categories.

- Raked windows are available, speak to your sales consultant about size limitations:

